



RAINBOW

MOISTURE-CURED POLYURETHANE PRIMER FOR WATER PROOF

PRODUCT NUMBER	785
TYPE	The one-pack clear coating based on special polyisocyanate resin.
USES	Primer for roofs, balconies, bathrooms, air garden etc, special suitable for cement walls, cement pipes and cement products. Scope of application: cement wall, cement pipelines and cement products.
CHARACTERISTICS	<ol style="list-style-type: none">1. One-pack polyurethane and easy application.2. Can penetrate into cement surface.3. Can be easily coated by the product number 777 and 789.4. Excellent adhesion with cement surface.
COLOR	Clear
SPECIFIC GRAVITY	Above 0.9 Kg/L
VISCOSITY	20 ~ 60 cps (25°C)
NON-VOLATILE CONTENTS	Above 40%
DRYING TIME	Set-to-touch 1 hr. Dry hard 4 hrs. Fully cured 7 days (25°C)
OVERCOATING INTERVALS	Min. 1 hr. Max. 2 days (25°C)
OPTIMUM FILM THICKNESS	Wet 100 microns Dry 32 microns
THEORETICAL COVERAGE	10.0 m ² /Kg 0.10 Kg/m ² (Reference amount : Coverage area of per 10 Kg are about 50~66 m ²)
THINNER	No.736 Polyurethane Thinner (cleaning tools only)
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Brush, Roller
NOTE	<ol style="list-style-type: none">1. Adhered moisture, grease, dust and rust on substrate must be cleaned thoroughly.2. The paint poured out the barrel do not recycle use to ensure quality.3. Consult your local representatives for the waterproofing system best suited for the surfaces to be protected.4. Applied as thinly as possible using a paint bush(or roller)and distributed evenly by over brush (or roller).
REMARKS	The practical spreading rate depends on a number of factors : surface condition and weather condition . It is often various from the theoretical spreading rate.

EPDM270785XX V1.3

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443