

CONTITHINNER 64 (1564X) HEAT-RESISTING THINNER FOR AMBIENT

TYPE

CONTITHINNER 64 is specially designed for Continental heat-resistance coating in ambient condition. (Subject's temperature is at 50°F (10°C) ~120°F (100°C) In addition to adjusting the coating viscosity, the thinner also can clean spray application equipment.

PRACTICAL INFORMATION

Color clear

MIXING & THINNING

Mixing Thoroughly mix to a uniform consistency prior to use.

Thinning Substrate temperature at room temperature~ 212°F (100°C) : Use 1564X to be thinner.
Substrate temperature at 214°F (101°C) ~392°F (200°C) : Use 1564S to be thinner.

CLEANER & SAFETY

Cleaner Use Thermal Thinner (CONTITHINNER 64X) to clean. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

Safety Ventilation Please read and follow all caution statements on this product data sheet and MSDS for this product.
Proper ventilation and protective measures must be provided during application and drying to keep solvent vapor concentrations within safe limits and to protect against toxic or oxygen deficient hazards.

PACKAGE, HANDLING & STORAGE

Shelf Life Minimum 24 months under normal conditions.

Shipping Weight 1 Gallon Kit – 3.3 kg
5 Gallon Kit – 16.5 kg

Storage Temperature & Humidity 41-95°F (5-35°C)
0-90% Relative Humidity

Storage Store in cool ventilated place, do not exposed to the sun in outdoor to avoid affecting the quality.