



RAINBOW

RAINBOTHERM 520

Heat-resist Paint (200°C)

PRODUCT NUMBER	RAINBOTHERM 520
TYPE	Heat resistant paint based on special resins with aluminium pigment.
CHARACTERISTICS	<ol style="list-style-type: none">1. Heat resisting paint for generators, chimneys and other high temperature in chemical and steel works.2. Good heat resistance stand to 200°C.3. Good weather resistance.4. Good oil and sea water resistance.5. Good adhesion.6. Easy application.
GLOSS	Gloss
COLORS	Aluminum
VOLATILE ORGANIC COMPOUND CONTENT	VOC 700 (g/l) below
PRODUCT WEIGHT	Above 1.0 kg/L
DRYING TIME	Set-to-touch 2 hrs Dry hard 4 hrs (25°C)
OPTIMUM FILM THICKNESS	Dry 25 Micron)
VOLUME SOLID	37±2 %
THEORETICAL COVERAGE	47.3 m ² /Gal 12.5 m ² /L
OVERCOATING TABLE	Min. 16 hours
THINNER	No. 1521 Paint Thinner
THINNER RATE	0~2% (by bush and roller) 0~3% (Airless)
RECOMMENDED SPEC.	Please refer the painting specification
SHELF LIFE	Minimum one year under normal storage condition
APPLICATION METHOD	Airless spray, Bush and Roller
NOTE	<ol style="list-style-type: none">1. Adhered water, grease and dust on substrate must be thoroughly clean.2. Substrate temperature should be 3°C above dew point, rainy day and relative humidity during application and curing should be below 85%, or job is to be stopped.3. Whilst application in the confine space, adequate ventilation must be maintenance.

EPDM3030520X V1.1

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443