



RAINBOW

WATER-BASED ELASTOMERIC CAULK

PRODUCT NUMBER	422
TYPE	The low contraction and high flexibility of elastomeric caulk based on water-based elastic resin with pigments and additives.
USES	Used for cement wall or wood to seal the cracks.
CHARACTERISTICS	<ol style="list-style-type: none">1. Match No.420/421 painting system, if there are bigger cracks (>1mm) that can be enhanced by this paint.2. High solids content, can obtain paint film of high paint film thickness and low contraction.3. Excellent adhesion and easy application.4. Excellent resistance to water and alkali.5. Elongation up to 200%.
FINISH	Flat
COLOR	White
MASS DENSITY	Above 1.3 Kg/L
VISCOSITY	Paste
DRYING TIME	Set-to-touch 5 hrs. (25°C, RH = 60%)
OPTIMUM FILM THICKNESS	Wet 4 m/m Dry 3 m/m
THEORETICAL COVERAGE	0.94 m ² /Gal 0.25 m ² /L @D.F.T. 3m/m
OVERCOATING INTERVALS	Min. 8 hrs.
THINNER	Tap Water
SUBSEQUENT COATS	No.421 Water-based elastomeric coating or emulsion paints
STORAGE SHELF LIFE	Minimum 2 years under normal storage conditions.
APPLICATION METHOD	Trowel
NOTE	<ol style="list-style-type: none">1. Adhered moisture, grease, and dirt on substrate must be cleaned thoroughly.2. Leveling surface of sealant before curing.

EPDM410422XX V1.0

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443