



# RAINBOW

## SUPER ALKYD VARNISH

PRODUCT NUMBER	601
TYPE	The varnish based on phenolic resin and dried oils.
USES	Used for wood furniture, rattan handicraft and indoor decoration.
CHARACTERISTICS	<ol style="list-style-type: none"><li>1. High gloss with good appearance.</li><li>2. Transparent finish can let wood grain clearly.</li><li>3. Good abrasion resistance.</li><li>4. Good water resistance particularly suitable for the wood products.</li><li>5. Easy application.</li></ol>
APPEARANCE	Transparent liquid
MASS DENSITY	Above 0.85 Kg/L
VISCOSITY	55~65 KU (25°C)
DRYING TIME	Set-to-touch 1 hr.                      Dry hard 6 hrs. (25 °C)
OPTIMUM FILM THICKNESS	Wet 50 microns                      Dry 25 microns
THEORETICAL COVERAGE	75.0 m <sup>2</sup> /Gal      20.0 m <sup>2</sup> /L      23.0 m <sup>2</sup> /Kg
OVERCOATING INTERVALS	Min. 12 hrs.
VOLUME SOLIDS	Above 50%
THINNER	No.805 Paint Thinner (OM-07)
THINNER RATE	0~5% (cleaning tools excluded)
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Brush, Spray, Roller.
NOTE	<ol style="list-style-type: none"><li>1. Adhered moisture, grease, and rust on the substrate must be removed thoroughly.</li><li>2. Firstly grind rough surfaces or old paint film use the #180~240 sandpaper before applying.</li><li>3. Avoid applying to insufficient drying of previous paint coats.</li></ol>

EPDM060601XX V1.0

## YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.  
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181  
FAX:886-7-8715443