



RAINBOW

WATER-BASED TOP COATING

PRODUCT NUMBER	406FM
TYPE	The paint based on the alkali resistance and excellent weathering of pure acrylic resin along with special pigments and additives.
USES	Decorating and protecting fire-retardant coating and interior and exterior wall.
CHARACTERISTICS	<ol style="list-style-type: none">1. Use water thinner without any pollution.2. Excellent weathering . resistance.3. Excellent water and alkali resistance.
COLOR	White and desired color
WEIGHT	Above 1.1 kg/L
VISCOSITY	85~110 KU
DRYING TIME	Set-to-touch 1/2 hrs. Dry through 2 hrs (RH=60%)
OPTIMUM FILM THICKNESS	Wet 85 μ (microns) Dry 35 μ (microns)
THEORETICAL COVERAGE	44.5 m^2 /Gal 11.8 m^2 /L
OVERCOATING INTERVALS	Min. 3 hrs.
THINNER	Tap Water
PRIMER	FM906-406FM-406FM FW30-406FM-406FM
THINNER RATE PRECEDING COATS	5~15%
STORAGE SHELF LIFE	Minimum 2 year under normal storage conditions.
APPLICATION METHOD	Spray,Brush,Roller
NOTE	<ol style="list-style-type: none">1. Before application, stir paint evenly. When paint is thick, water can be added according to specified quantity.2. Water content in new cast cement wall must be lower than 12% ;otherwise, it will reduce adhesion and performance of paint film.3. The moisture, grease and dirt, dust and other contaminants on applied surface must be clean thoroughly.

EPDM410406FM V1.0

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26,Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443