

FLAT PAINT, WHITE

PRODUCT NUMBER	2301
TYPE	Flat topcoat based on special synthetic resin with titanium dioxide pigment.
USES	Used for ship's living place and house's or shop's indoor to decoration.
CHARACTERISTICS	1. Drying fast and excellent adhesion.
	2. Soft and flat film.
	3. Excellent resistance to moisture, water and salt water.
	4. Tough film with excellent abrasion.
	5. Easy application.
FINISH	Flat
COLOR	White
HIDING POWER	Above 10 m ² /L
MASS DENSITY	Above 1.3 Kg/L
VISCOSITY	70~90 KU (25℃)
DRYING TIME	Set-to-touch 1/2 hr. Dry hard 3 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 100 microns Dry 40 microns
THEORETICAL COVERAGE	38.0 m²/Gal 10.0 m²/L 7.7 m²/Kg
OVERCOATING INTERVALS	Min. 4 hrs.
NON-VOLATILE CONTENT	Above 60%
THINNER	No.805 Paint Thinner (OM-07)
THINNER RATE	5 ~ 10% (tools cleaning excluded)
PRECEDING COATS	No.404 Solvent-based Acrylic Primer
	No.410-1 Emulsion Primer
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Spray, Brush, Roller.
NOTE	1. Before application, stir paint evenly, and when paint is too thick, the thinner within
	specified quantity can be added.

2. Adhered moisture, grease, and dirt on substrate must be cleaned thoroughly.

EPDM012301XX V1.1

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26,Yen Hai 3rd Road, Kaohsiung, Taiwan. http://www.rainbowpaint.com.tw TEL:886-7-8713181 FAX:886-7-8715443