



RAINBOW

POLYVINYL ESTER PUTTY

PRODUCT NUMBER	1613
TYPE	Two component type of polyvinyl resin with a special filler pigment and an initiator.
USES	Mechanical products, casting parts and putty for metal of car or ship.
CHARACTERISTICS	<ol style="list-style-type: none">1. Dry fast, suitable for severe corrosive environments.2. Good adhesion and flexible, excellent adhesion to metal surface and cement surface, no cracking, no peeling.3. Excellent resistance to moisture, water and good for anticorrosion.4. Easy to grind, not affected by the difference between cold and hot.5. Free of volatile solvents, the coating will not cause any shrink.6. Excellent acid and alkali resistance.
COLOR	Light Grey
APPEARANCE	Paste
GRINDABLE TIME	At least 2 hrs. (25°C)
OVERCOATING INTERVALS	Min. 2 hrs. Max. 10 days (25°C)
MIXING RATIO	Base : hardener = 100 : 1 (in summer time) (by weight) Base : hardener = 100 : 2 (in summer time) (by weight)
POT LIFE	25 minutes Maximum (25°C)
CLEANNER	No.719 Thinner and Detergent for Polyvinyl Resin
HEAT RESISTANCE	180°C Maximum (dry environment)
STORAGE SHELF LIFE	Maximum 12 days (under 30°C storage conditions.) Maximum 30 days (under 25°C storage conditions.) Maximum 90 days (under 5°C storage conditions.)
APPLICATION METHOD	(trowel / filling knife)
NOTE	<ol style="list-style-type: none">1. Moisture, grease, dust, rust, etc. on the surface of the object to be coated must be removed.2. Mix base and hardener according to the mixing ratio and stir thoroughly and then apply within 10 minutes.3. The protruding matter should be flattened before it is hardened.4. Please store in a cool, ventilated place to prevent paint from hardening.5. When applied to internal tanks, sufficient ventilation must be provided.6. Substrate temperature during application and curing should be above 5°C.7. Do not apply the product to other types of paint, which may cause damage to the paint.

EPDM701613XX V1.1

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443