



# RAINBOW

## THREE-DIMENSIONAL TEXTURE PAINT

PRODUCT NUMBER	NO.8513
TYPE	It is made of water-based high weather-resistant acrylic resin, combined with weather-resistant pigments and special additives, and is specially designed for outdoor harsh environments.
USES	Exterior wall paint combining beauty and function.
CHARACTERISTICS	<ol style="list-style-type: none"><li>1. Water-based environmental protection coating, easy to apply.</li><li>2. Excellent weather resistance.</li><li>3. Excellent waterproof and breathability.</li><li>4. Good alkali resistance, water resistance, algae resistance, mildew resistance.</li><li>5. Three-dimensional texture modeling.</li></ol>
COLOR	Various colors
MASS DENSITY	Above 1.18 Kg/L
DRYING TIME	Set-to-touch 1/2 hr.      Dry hard 3 hrs. (25 °C)
THEORETICAL COVERAGE	1.8 m <sup>2</sup> / kg (The actual dosage is mainly based on site modeling)
OVERCOATING INTERVALS	Min. 6 hrs.
NON-VOLATILE CONTENT	Above 50.0%
THINNER	Tap water
THINNING RATE	0~5%
STORAGE SHELF LIFE	Minimum 2 years under normal storage conditions.
APPLICATION METHOD	Roller coating (professional tool: brush roller, please contact us), Spraying (professional tool: stone paint spray gun).
APPLICABLE TRANSPARENT FINISH	ECO-102, ECO-202
APPLICABLE PRIMER	NO.467, NO.467+NO.467AD(Recommended Use)
PRECAUTIONS	<ol style="list-style-type: none"><li>1. Stir well before use.</li><li>2. The grease, dust, moisture and other attached dirt on the surface of the coated object must be removed before construction.</li><li>3. The new cement wall contains a lot of water and free alkaline, which will reduce the performance and adhesion of the dry film. After drying, the moisture value is below 12%. After applying the primer, the topcoat can be applied.</li><li>4. Avoid construction when it is rainy or atmospheric relative humidity is above 85RH, especially when the surface is wet, it must be completely dried; It can be applied only when the surface temperature is between 5 °C~ 40 °C.</li></ol>
NOTE	The actual brushing area will be affected by the nature of the substrate, the substrate surface conditions, construction tools and other environmental factors.

EPDM858513XX V1.4

# YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.  
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181  
FAX:886-7-8715443