



RAINBOW

RUST PREVENTIVE OIL

PRODUCT NUMBER	610 (OM-06)
TYPE	The oil based on synthetic resin with rust inhibitive agent.
USES	Used for storage tank of mineral oil or fuel oil to do temporary rust prevention.
CHARACTERISTICS	<ol style="list-style-type: none">1. Very fast drying and good adhesion.2. Good water and corrosion resistance.3. Easily dissolved in mineral oil or fuel oil without any bad effects.4. Easy application.
APPEARANCE	Pale transparent liquid
FINISH	Gloss
FLASH POINT	Above 25°C (77°F)
MASS DENSITY	Above 0.90 Kg/L
VISCOSITY	50~60 KU (25°C)
DRYING TIME	Set-to-touch 1/2 hr. Dry hard 1 hr. (25°C)
OPTIMUM FILM THICKNESS	Wet 45 microns Dry 25 microns
OVERCOATING INTERVALS	Min. 2 hrs. (25°C)
VOLUME SOLIDS	Above 55%
THEORETICAL COVERAGE	84.0 m ² /Gal 22.2 m ² /L 24.7 m ² /Kg
THINNER	No.805 Paint Thinner (OM-07)
THINNING RATE	0~5% (by wt.)
STORAGE SHELF LIFE	Minimum 6 months under normal storage conditions.
APPLICATION METHODS	Airless Spray, Brush, Roller.
FOR AIRLESS SPRAY	Tip Size 0.015" ~ 0.019" Air Pressure 4 ~ 5 Kg/cm ² Pump Ratio 23 : 1 or greater

EPDM060610XX V1.0

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443