



RAINBOW

M.I.O. PRIMER

PRODUCT NUMBER	950
TYPE	Rust prevention middle primer based on alkyd resin and special resin with mica flake iron oxide, aluminum powder pigments.
USES	Used for steel structures, bridges and storage tanks.
CHARACTERISTICS	<ol style="list-style-type: none">1. Very fast drying with good adhesion.2. Excellent resistance to water and oils.3. Excellent rust resistance, dipping in 3% salt water for 120 hours, result had no abnormal.4. Excellent ultraviolet resistance and permeability.
FINISH	Flat
COLOR	Silver Red
HIDING POWER	Above 20.0 m ² /L
MASS DENSITY	Above 1.4 Kg/L
VISCOSITY	80~100 KU (25°C)
DRYING TIME	Set-to-touch 1 hr. Dry hard 3 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 125 microns Dry 50 microns
THEORETICAL COVERAGE	30.3 m ² /Gal 8.0 m ² /L 5.3 m ² /Kg
OVERCOATING INTERVALS	Min. 4 hrs.
NON-VOLATILE CONTENT	Above 60%
THINNER	No.805 Paint Thinner (OM-07)
THINNING RATE	5~10% (cleaning for tools not included)
PRECEDING COATS	No.904 Red Oxide Primer (OP-95) No.905 High Red Lead Primer (OP-91) No.906 Red Lead Primer (OP-92) No.907 Zinc Chromate Primer (OP-93) No.911 Red Lead Primer, General Purpose (SP-70) No.920 LZI Primer (OP-94) No.992 Aluminum Tripolyphosphate Primer Ready-Mixed Paints, Synthetic Enamels
SUBSEQUENT COATS	
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Spray, Brush, Roller
NOTE	<ol style="list-style-type: none">1. Before application, stir paint evenly, and when paint is too thick, thinner within specified quantity can be added.2. Adhered moisture, grease, dirt, damaged or loose old paint and corrosive salts on substrate must be cleaned thoroughly.3. Avoid applying the paint in rainy, humid weather or substrate temperature excessively high to 40°C or low to 10°C.4. Avoid applying to insufficient drying of previous paint coat.

EPDM090950XX V1.0

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443