



RAINBOW

RAINBOW Pro Stone Paint

PRODUCT NUMBER	NO.8516
TYPE	RAINBOW Pro Stone Paint is made of water-based high-quality weather-resistant resin and inorganic colored sand, together with high-quality additives.
USE	Used for building exterior walls, line panels, special decorative materials and molding materials and other objects. Applicable building types: buildings, villas, commercial offices, homestays/restaurants, public buildings, etc.
CHARACTERISTICS	<ol style="list-style-type: none">1. Granite texture.2. Lightweight and safe.3. Stone textured and flexible coating.4. Good weather resistance.5. Convenient construction.
PRODUCT SERIES	Sand surface(18 colors) Glazed surface(12 colors)
DRYING TIME	Set-to-touch 1.5 hrs. Dry hard 4 hrs. (25°C)
THEORETICAL COVERAGE	2.7-3.4 m ² /kg
OVERCOATING INTERVALS	Min. 6 hrs.
THINNER	Tap water
APPLICABLE CLEAR TOPCOAT	ECO102 All-Weather Dirt Shedding Clear Paint
PRECEDING COATS	No.467 Water Base Penetrating Waterproof Sealer (No.467 matched with No.467AD use to have better effects.)
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Brush, spray, roller (Need to be applied 2- or 3-coats.)
NOTE	<ol style="list-style-type: none">1. Need to match RAINBOW PRO STONE PAINT SYSTEM.2. Stir well before use and do not use an electric mixer.3. The grease, dust, moisture and other attached dirt on the surface of the coated object must be removed before construction.4. The new cement wall contains a lot of water and free alkaline, which will reduce the performance and adhesion of the dry film. After drying, the moisture value is below 12%. After applying the primer, the topcoat can be applied.5. Avoid construction when it is rainy or atmospheric relative humidity is above 85RH, especially when the surface is wet, it must be completely dried; It can be applied only when the surface temperature is between 5°C ~ 40°C. <p>The actual brushing area will be affected by the nature of the substrate, the substrate surface conditions, construction tools and other environmental factors.</p>

EPDM858516XX V1.0

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26,Yen Hai 3rd Road, Kaohsiung, Taiwan. TEL:886-7-8713181
<http://www.rainbowpaint.com.tw> FAX:886-7-8715443