



RAINBOW

WATER BASED PENETRATING WATERPROOF SEALER

PRODUCT NUMBER	NO.467
TYPE	The Penetrating Waterproof Sealer based on excellent water and alkali resistant water-based acrylic resin and filler.
USES	It is a special high-permeability primer for indoor and outdoor walls, cement surfaces, and concrete. The surface of the tiles must be mixed with 467AD Adhesion Promoter For Sealer.
CHARACTERISTICS	<ol style="list-style-type: none">1. Very fast drying, easy application.2. Good permeability and strong adhesion.3. Dry quickly and excellent workability.4. Alkali resistance is excellent.5. Simple construction and excellent water resistance.
GLOSS	gloss
COLOR	Semi-transparent
MASS DENSITY	Above 1.02 Kg/L
DRYING TIME	Set-to-touch 1/2 hr. Dry hard 3 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 90 microns Dry 10- 20 microns
THEORETICAL COVERAGE	49.5 m ² /Gal 13.1 m ² /L
OVERCOATING INTERVALS	Min. 4 hrs.
NON-VOLATILE CONTENT	Above 28.0%
THINNER	Tap water
THINNING RATE	10~35%
SUBSEQUENT COATS	NO.424 、 NO.421 、 NO.406 、 SA2000 、 SA3000 、 SA5000 、 NO.8513.
STORAGE SHELF LIFE	Minimum 3 years under normal storage conditions.
APPLICATION METHOD	Spray, Brush, Roller.
INSTRUCTIONS & PRECAUTIONS	<ol style="list-style-type: none">1. The new cement contains a large amount of water and free alkali substances, which will reduce the performance and adhesion of the paint. It must be cured for 2 to 3 weeks. After it is completely dry, the moisture content is below 12 % and it can be applied.2. Avoid construction when it is rainy or atmospheric relative humidity is above 85RH. When the surface is wet, it must be completely dry; when the surface temperature is between 5°C-40°C, construction can be started.3. Please stir the product evenly before use. The grease, dust, moisture and other attached dirt on the surface of the coated object must be removed before construction.4. If the surface of the substrate is loose, it is recommended to add water to dilute it by 30~35% to enhance the permeability and the adhesion of the substrate.5. If the surface of the coating is severely powdered, apply primer several times.
NOTE	The actual brushing area will be affected by the nature of the substrate, the substrate surface conditions, construction tools and other environmental factors.

EPDM410467XX V1.4

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443