GALVANIZED STEEL EMULSION PAINT

PRODUCT NUMBER 500P

TYPE Emulsion corrosion prevention primer based on water-based acrylic resin with

rust resistant pigment and special additives.

USES Used for galvanized iron sheets, galvanized equipments, galvanized iron pipes,

galvanized corrugated iron sheets, galvanized steel structures and general steel

structures.

CHARACTERISTICS 1. Strong adhesion with galvanized iron sheet, without need to coat pretreatment

agent.

2. Excellent resistance to rust and corrosion.

3. Excellent resistance to water and chemicals.

4. Odorless, flavorless, non-pollution.

5. Excellent hiding power and brush ability.

6. Direct application over steel surfaces without rust stains.

7. Easy to apply, tools can be water washable.

FINISH Semi-gloss

COLOR White or desired colors.

HIDING POWER Above 8.0 m²/L MASS DENSITY Above 1.2 Kg/L VISCOSITY 60~90 KU (25°C)

DRYING TIME Set-to-touch 1 hr. Dry hard 4 hrs. (25°C)

OPTIMUM FILM THICKNESS Wet 80 microns Dry 30 microns

47.3 m²/Gal 12.5 m²/L THEORETICAL COVERAGE

OVERCOATING INTERVALS Min. 6 hrs. NON-VOLATILE CONTENTS Above 45%

THINNER Tap water (only for rinsing tools)

PRECEDING COATS Rainbow Brand Ready Mixed Paint, C.R. Paint, All-Purpose Paint or

No.1030 Water-based Catalyzed Epoxy Topcoat

STORAGE SHELF LIFE Minimum 2 year under normal storage conditions.

APPLICATION METHOD Brush, Roller, Airless Spray.

> 1. Before application, stir paint evenly. Do not add extra thinner to the paint for avoid reducing adhesion and anti-corrosion abilities due to insufficient thickness of paint film.

2. Adhered moisture, grease, rust, dirt and loose paints film on substrate must be removed thoroughly.

3. Subsequent coat has to wait until paint films of preceding coat completely dry off.

4. Avoid applying the paint in rainy weather or humidity above 85% RH, particularly a wet surface must be thoroughly dried.

EPDM41500PXX V1.1

NOTE

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan. TEL:886-7-8713181 http://www.rainbowpaint.com.tw

FAX:886-7-8715443