RAINBOW RAINBOW

SOLVENT-BASED ACRYLIC PAINT, GOLDEN

PRODUCT NUMBER.	417
ТҮРЕ	The solvent-based acrylic paint based on weather and alkali resistant acrylic resin
	with golden pigment.
USES	Used for cement columns and cement products.
CHARACTERISTICS	1. Very fast drying, good workability and excellent color retention, non-blacking.
	2. Excellent moisture, weather resistance and gloss retention.
	3. Excellent alkalis resistance.
COLOR	Golden
MASS DENSITY	Above 1.0 Kg./L
VISCOSITY	80~100 KU (25℃)
DRYING TIME	Set-to-touch $1/2$ hr. Dry hard 2 hrs. $(25^{\circ}C)$
OPTIMUM FILM THICKNESS	Wet 85 microns Dry 35 microns
THEORETICAL COVERAGE	44.7 m [*] /Gal 11.8 m [*] /L
OVERCOATING INTERVALS	Min. 3 hrs. (25℃)
NON-VOLATILE CONTENTS	Above 50%
THINNER	NO.807 Xylene
THINNING RATE	5~10%
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions
APPLICATION METHOD	Spray, Brush, Roller
NOTE	1. The moisture content of new constructed cement walls should be under 12%. If not,
	the application has to wait for 2 or 3 weeks until the wall is dry completely.
	Otherwise, too much moisture and alkali may affect film's performance and
	adhesion.

2. Adhered moisture, grease, and dirt on substrate must be cleaned thoroughly.

EPDM040417XX V1.1

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan. TEL:886-7-8713181 http://www.rainbowpaint.com.tw

FAX:886-7-8715443